element iconv
xdebug
algorithm
stream
csr
call
handler dtd pkey
algorithm debug proc
enc
encrypt
timezone
current encode bucket
mcrypt
write call unregister
public
pkcs7 func libxml memory cdata status convert
contents
date hash
exists multi decrypt
default
data
openssl
session guid
module parse
file socket
data mime
preg clean
print simplexml
dump
add
cal var exists num
xmlrpc xml list
curl
string filter
autoload autoload headers x509
comment
attlist
export exec
defined
field ns
xmlwriter
time
pi
get
function ctype
copy
assoc
client coverage uassoc dir replace create entity user
db
path
class
encoding
blocking
open
mode
split
id
ob
array
magic
connect
odbc
result
spl
logo size
generic
fetch name
object end start
code
info init
decl
set ftp
query
variant
mysql
nb
quotes
register
parser
attribute
close decode
com type
private vars replace wrapper ini
diff
declared
wddx intersect
size key
substr restore php
block
unregister
error

preg
get
variant
error
attribute
simplexml
restore
user
split
diff
contents
autoload
mode
path
debug
session
xml
call
close
encode
hash
field
private
algorithm
set
ftp
dump
object
vars
result
assoc
register
replace
cal
parse
current
mime
list
element
create
exists
key
file
decode
spl
blocking
substr
connect
ns
decrypt
libxml
size
info
db
pkey
func
open
coverage
logo
declared
curl
xdebug
start
ob
wrapper
time
exists
encrypt
headers
enc
id
php
ini
var
handler
size
pi
uassoc
public
init
clean
parser
pkcs7
block
csr
x509
quotes
algorithm
xmlwriter
odbc
write
guid
function
dir
code
print
com
replace
generic
xmlrpc
fetch
default
mcrypt
date
decl
client
end
timezone
call
attlist
status
socket
query
add
wddx
comment
class
module
ctype
exec
cdata
export
bucket
name
multi
string
num
unregister
memory
data
intersect
stream
iconv
proc
type
filter
dtd
data
encoding
magic
defined
convert
unregister
nb
arrayy
openssl
mysql