element
iconv
xdebug
call
csr
timezone
current
encode
bucket
contents
stream
algorithm
handler
dtd
pkey
proc
debug
algorithm
enc
encrypt
mcrypt
write
call
unregister
default
public
pkcs7
func
libxml
memory
cdata
status
convert
date
hash
exists
multi
decrypt
data
openssl
session
guid
module
parse
file
socket
data
mime
preg
clean
dump
print
simplexml
add
xmlrpc
xml
list
curl
string
filter
autoload
autoload
headers
x509
cal
var
exists
num
comment
attlist
xmlwriter
export
exec
defined
field
ns
time
pi
get
function
ctype
path
copy
class
assoc
encoding
coverage
uassoc
dir
replace
create
entity
user
db
open
mode
split
id
array
ob
result
blocking
magic
connect
odbc
spl
logo
size
generic
fetch
name
object
end
start
code
info
init
decl
set
ftp
query
variant
mysql
register
nb
quotes
parser
attribute
com
type
close
decode
private
vars
replace
wrapper
ini
diff
declared
wddx
intersect
substr
restore
php
size
key
block
unregister
error

preg
get
array
openssl
mysql
xmlwriter
odbc
stream
mcrypt
xdebug
set
ftp
session
xml
variant
error
date
name
export
dtd
data
size
info
libxml
decrypt
parse
mime
current
cal
connect
ns
db
pkey
func
element
create
exists
key
file
hash
encode
call
close
field
decode
curl
start
ob
block
xmlrpc
fetch
timezone
end
socket
string
multi
status
cdata
bucket
decl
replace
com
uassoc
public
init
pi
clean
parser
pkcs7
generic
client
entity
csr
x509
quotes
algorithm
wrapper
time
spl
logo
declared
coverage
private
open
split
diff
restore
user
attribute
simplexml
autoload
contents
mode
path
debug
dump
object
vars
assoc
result
register
replace
blocking
substr
headers
copy
id
enc
write
var
dir
guid
function
class
module
type
handler
ini
php
code
print
ctype
exec
filter
proc
unregister
nb
encrypt
exists
icon
convert
wddx
comment
attlist
default
num
unregister
memory
query
add
intersect
data
defined
magic
encoding